



Neutral active cleaner RM 55 ASF

All-purpose and gentle liquid high-pressure cleaning concentrate for use on heavy grease and oil soiling and soiling caused by emissions. Excellently suited to façade cleaning and to cleaning sensitive surfaces. NTA free.





Properties

- Universal high-pressure cleaning agent
- Dissolves oil, grease and mineral stains
- Very good cleaning properties, particularly with cold water
- Gentle cleaning action
- Pleasant, fresh fragrance
- Tensides biodegradable in accordance with EEC 648/2004
- Rapidly separates oil/water in the oil separator (easy to separate=asf)
- NTA free
- Silicone free
- suitable for alkali-sensitive surfaces (e.g. aluminium)

Areas:

Transport and transportation equip-Agriculture:

Car dealership and garage: Car/engine wash Car dealership and garage: Parts cleaning

Transport and transportation equip-**Building Industry:**

ment

Contract cleaning: Façade cleaning Municipal: Car/engine wash

Haulage contractors, bus oper-

Car/engine wash

Application

- High-pressure washers
- Spray units
- Manual

	Part number		
2.5	6.295-579.0		
10	6.295-090.0		
20	6.295-411.0		
200	6.295-412.0		
1000 I	6.295-093.0		

рΗ







Application:

High-pressure washers

- Set the dosage and temperature on the device
- 1-80°C processing temperature.
- \blacksquare Clean object, working in overlapping sections.
- Rinse surface well with clear water.

Spray attachment

- Combine the product with the appropriate dosage and fresh water.
- Wet object completely with product.
- Allow to soak.
- Reaction time 1-5 minutes, depending on the degree of soiling.
- Rinse with clear water.

Manual

- Combine the product with the appropriate dosage and fresh water.
- Clean object.
- Rinse with clear water.

Directions for use:

Store away from frost.

Warnings and safety recommendations according to EC Directives:

■ EUH 210 Safety data sheet available on request.

Further information:

■ Material Safety Data Sheet (MSDS)

Dosage and yield:

Content:	Cleaning method:	Primary mixture:	Dosage:	Contamination:	Productivity:
1000 ml	High-pressure washers		0.5-8 %		130 m²
1000 ml	Spray units		10 %		110 m²
1000 ml	Manual		2 %		125 m²

Please contact us for more information:

Kärcher (UK) Ltd

Kärcher House Brookhill Way Banbury Oxon OX16 3ED

T: +44 1295 752 000 E: enquires@karcher.co.uk